

客户 Customer: _____

日期 DATE: _____

纳入仕様书

SPECIFICATION

产 品 名 称 PRODUCT NAME: 声表滤波器

SAW Filter

贵 司 料 号 YOUR PART NO.: _____

敝 司 料 号 OUR PART NO.: MS11U2G15-RX66C

版 本 号 VERSION.: V1.1

接受 RECEPTION

THE SPECIFICATION HAS BEEN ACCEPTED.

该纳入仕様书已被我司接受

日期:
DATE:公司:
COMPANY:批准
CFMD审核
CHKD接收
RCVD

深圳市麦捷微电子科技股份有限公司
SHENZHEN MICROGATE TECHNOLOGY CO., LTD
TEL: 86-755-28085000
FAX: 86-755-28085605

CFMD. 批准	CHKD. 审核	DSGD. 担当
赵拥军	赖定权	赵新佳

深圳市麦捷微电子科技股份有限公司
地址: 深圳市坪山区坪山大道 6075 号龙田科技园二巷 6 号
电话(Tel): 0755-28085000 传真(Fax): 0755-28085605

邮编(Postcode): 518110

1

纳入仕様书改定履历

MODIFY HISTORY OF SPECIFICATION

NO.	修改日期/DATE	修改内容/CONTENT	批准/APPROVED
1.0	2020.6.22	初稿 /New Released	赵拥军
1.1	2021.7.19	版本升级/Version Upgrade	赵拥军

目录 CATALOG

1 适用范围 Scope.....	4
2 品名构成 Product Identification.....	4
3 尺寸和管脚定义 Dimensions and PIN Configurations.....	4
4 推荐焊盘与测试电路 Recommended Land Pattern and Test Circuit.....	5
5 电气性能 Electrical Characteristics.....	5
6 包装 Packaging.....	8
7 装箱清单及标志 Packing documents and marking.....	9
8 保管 Storage.....	11

1 适用范围 Scope

麦捷声表滤波器系列产品设计用于 WIFI、GPS、移动电话和无绳电话机等相关市场中。

Microgate SAW Component is applicable for WIFI/GPS/Mobile phone/Cordless phone relevant market.


2 品名构成 Product Identification

MS 11 U 2G15 - RX 66 C
① ② ③ ④ ⑤ ⑥ ⑦

- ① 麦捷声表滤波器/Microgate SAW
- ② 尺寸/Size: 11(20-2016, 18-1814, 15-1511, 14-1411, 11-1109)
- ③ 输出/Output: U(B-Balance out, U-Unbalance out)
- ④ 频率/Frequency: 2G15-2.155GHz
- ⑤ 型号/Type: RX(QP-QPX, DU-Duplexer, DI-Diplexer, TX-TX SAW, RX-RX SAW)
- ⑥ 频段/Band: 66-Band66
- ⑦ 流水号/Serial number

3 尺寸和管脚定义 Dimensions and PIN Configurations

Unit:mm



PIN NO.	(1)	(2)	(3)	(4)	(5)
PIN Name	Input	GND	GND	Output	GND

深圳市麦捷微电子科技股份有限公司

地址: 深圳市坪山区坪山大道 6075 号龙田科技园二巷 6 号

电话(Tel): 0755-28085000


传真(Fax): 0755-28085605

邮编(Postcode): 518110

4 推荐焊盘与测试电路 Recommended Land Pattern and Test Circuit


Land Pattern

Unit:mm



Test Circuit

Bottom View



5 电气性能 Electrical Characteristics

操作温度范围 Operating Temperature Range : -30 to +85°C

保存温度范围 Storage Temperature Range : -40 to +85°C

湿度敏感等级 Moisture Sensitivity Level: MSL 2a

静电敏感等级 Electrostatic Discharge(ESD) Sensitivity: 250V (Human Body Model)

端口电压 D.C. Volatage between the terminals: 3V (25°C±2°C)

Table1. Electrical Specification

No.	Item		Frequency (MHz)	Specification			
				Min	Typ.	Max	Unit
1	ANT to Rx	Insertion Loss	2110~2200		2.8	3.5	dB
2		Ripple Deviation	2110~2200		1.6	2.5	dB
3		Absolute Attenuation	10~699	30	41		dB
4			10~190	50	75		dB
5			10~400	40	55		dB
6			699~716	30	40		dB
7			777~787	30	38		dB
8			810~814	30	37		dB
9			814~849	30	37		dB
10			880~915	30	35		dB
11			898~925	25	35		dB
12			1710~1780	26	33		dB
13			1730~1920	23	34		dB
14			1920~1980	28	36		dB
15			2015~2075	22	32		dB
16			2285~4000	15	28		dB
17			2400~2500	30	41		dB
18		VSWR	2110~2200（Input）		1.8	2.2	
19			2110~2200（Output）		1.8	2.2	
20	Input Signal Level		2110~2200（Input）	+15dBm	Continuous wave for 2000h(55℃)		

深圳市麦捷微电子科技股份有限公司

地址: 深圳市坪山区坪山大道 6075 号龙田科技园二巷 6 号

电话(Tel): 0755-28085000


传真(Fax): 0755-28085605

邮编(Postcode): 518110

5

Frequency Performance

Frequency Response



深圳市麦捷微电子科技股份有限公司


地址：深圳市坪山区坪山大道 6075 号龙田科技园二巷 6 号

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

VSWR



深圳市麦捷微电子科技股份有限公司

地址：深圳市坪山区坪山大道 6075 号龙田科技园二巷 6 号


电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110


6 包装 Packaging

① 编带尺寸 Dimensions of Tape:



② 带轮尺寸 Dimensions of Reel


Unit: mm



A	178±2
B	60±2
C	13.0±0.5
D	21.0±0.8
E	2.0±0.5
W	8.5±1.0
t	1.2±0.2
R	1.0±0.25

Reel material: PS (Polystyrene)

③ 编带简图及拉伸方向 Taping figure and drawing direction:



深圳市麦捷微电子科技股份有限公司

地址: 深圳市坪山区坪山大道 6075 号龙田科技园二巷 6 号



电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

8

检验合格后,检验员在标签上盖上合格章。合格章如下所示: The eligible reels will be pressed a mark onto the surface. The mark will be as following:




③ 内包装盒标记:Marking on inner box

- a.型号 MICROGATE part No.
- b.每盒数量 Quantity per box
- c. 包装日期 Date

以上内容必须在标签上注明 (标签见 7.2 所示)。Above shall be shown on marking label (The marking label is shown in item 7.2).

④ 外包装箱标记 Marking on outer case:

- 1) 制造商 Manufacturer: “MICROGATE” ①
- “中国深圳制造” “Made in Shenzhen CHINA”②
- 2) 发运标记 Ship marking:
“向上” “UP”, “小心轻放”“HAND CARE”, “防潮”“MOISTURE-PROOF”.
- 3) 包装标签包括以下内容 Packing label include the following:
 - a.型号 MICROGATE Part No
 - b.总数量 Total quantity per case
 - c.包装日期 Date;



以上内容必须在标签上注明。(参见 7.2 所示)

All above shall be shown on marking label. (The marking label is shown in item 7.2)

8 保管 Storage

保存条件 Storage conditions

- 存放货物的库房应满足以下条件 Products should be storage in the warehouse on the following conditions

温度 Temperature: $\leq 40^{\circ}\text{C}$

湿度 Humidity : $\leq 70\%$ relative humidity

不允许温、湿度有极剧变化。No rapid change on temperature and humidity

- 禁止将产品保管在腐蚀性物质中，例如硫磺、氯气或者酸，否则将引起端头氧化，导致降低焊接性。

Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solder ability.

- 为了避免受潮气、灰尘等物质的影响，产品应保管于货架上。Products should be storage on the palette for the prevention of the influence from humidity, dust and so on.

●产品保管在库房中时，应避免热冲击，振动以及直接光照等等。Products should be storage in the warehouse without heat shock, vibration, and direct sunlight and so on.

- 产品应密封包装 Products should be storage under the airtight packaged condition.