

客户 Customer: \_\_\_\_\_

日期 DATE: \_\_\_\_\_

# 纳入仕様书

## SPECIFICATION

产 品 名 称 PRODUCT NAME: 声表滤波器

SAW Filter

贵 司 料 号 YOUR PART NO.: \_\_\_\_\_

敝 司 料 号 OUR PART NO.: MS11U1G17-G5

版 本 号 VERSION.: V1.0

接受 RECEPTION

THE SPECIFICATION HAS BEEN ACCEPTED.

该纳入仕様书已被我司接受

日期:  
DATE:公司:  
COMPANY:批准  
CFMD审核  
CHKD接收  
RCVD

深圳市麦捷微电子科技股份有限公司  
SHENZHEN MICROGATE TECHNOLOGY CO., LTD  
TEL: 86-755-28085000  
FAX: 86-755-28085605

| CFMD.<br>批准 | CHKD.<br>审核 | DSGD.<br>担当 |
|-------------|-------------|-------------|
| 赵拥军         | 赖定权         | 吴继航         |

深圳市麦捷微电子科技股份有限公司  
地址: 深圳市龙华新区观澜街道高尔夫大道裕新路 65 号  
电话(Tel): 0755-28085000 传真(Fax): 0755-28085605

邮编(Postcode): 518110

纳入仕様书改定履历

**MODIFY HISTORY OF SPECIFICATION**

| NO. | 修改日期/DATE | 修改内容/CONTENT     | 批准/APPROVED |
|-----|-----------|------------------|-------------|
| 1.0 | 2020.5.8  | 初稿 /New Released | 赵拥军         |

## 目录 CATALOG

|   |                                                          |    |
|---|----------------------------------------------------------|----|
| 1 | 适用范围 Scope.....                                          | 4  |
| 2 | 品名构成 Product Identification.....                         | 4  |
| 3 | 尺寸和管脚定义 Dimensions and PIN Configurations.....           | 4  |
| 4 | 推荐焊盘与测试电路 Recommended Land Pattern and Test Circuit..... | 4  |
| 5 | 电气性能 Electrical Characteristics.....                     | 5  |
| 6 | 包装 Packaging.....                                        | 8  |
| 7 | 装箱清单及标志 Packing documents and marking.....               | 9  |
| 8 | 保管 Storage.....                                          | 11 |

## 1 适用范围 Scope

麦捷声表滤波器系列产品设计用于 WIFI、GPS、移动电话和无绳电话机等相关市场中。

Microgate SAW Component is applicable for WIFI/GPS/Mobile phone/Cordless phone relevant market.


## 2 品名构成 Product Identification

MS 11 U 1G17 - G 5  
① ② ③ ④ ⑤ ⑥

- ① 麦捷声表滤波器/Microgate SAW
- ② 尺寸/Size: 11(20-2016, 18-1814, 15-1511, 14-1411, 11-1109)
- ③ 输出/Output: U(B-Balance out, U-Unbalance out)
- ④ 频率/Frequency: 1G17(1G17-1.17GHz)
- ⑤ 型号/Type: G(GPS: Global Position System, 全球定位系统)
- ⑥ 频段/Band: L5

## 3 尺寸和管脚定义 Dimensions and PIN Configurations

Unit:mm




| PIN NO.  | (1)   | (2) | (3) | (4)    | (5) |
|----------|-------|-----|-----|--------|-----|
| PIN Name | Input | GND | GND | Output | GND |

## 4 推荐焊盘与测试电路 Recommended Land Pattern and Test Circuit


Land Pattern

Unit:mm



Test Circuit

Bottom View



深圳市麦捷微电子科技股份有限公司

地址: 深圳市龙华新区观澜街道高尔夫大道裕新路 65 号

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

## 5 电气性能 Electrical Characteristics

操作温度范围 Operating Temperature Range : -30 to +85°C

保存温度范围 Storage Temperature Range : -40 to +85°C

湿度敏感等级 Moisture Sensitivity Level: MSL 2a

静电敏感等级 Electrostatic Discharge(ESD) Sensitivity: 250V (Human Body Model)



端口电压 D.C. Volatage between the terminals: 3V (25°C±2°C)

Table1. Electrical Specification

| No. | Item         |                         | Frequency<br>(MHz) | Specification      |     |      |      |
|-----|--------------|-------------------------|--------------------|--------------------|-----|------|------|
|     |              |                         |                    | Min                | Max | Typ. | Unit |
| 1   | ANT to<br>Rx | Insertion Loss          | 1164~1189          |                    | 1.5 | 0.9  | dB   |
| 2   |              | Ripple Deviation        | 1164~1189          |                    | 1.0 | 0.4  | dB   |
| 3   |              | Absolute<br>Attenuation | 638~698            | 40                 |     | 46   | dB   |
| 4   |              |                         | 698~748            | 41                 |     | 47   | dB   |
| 5   |              |                         | 777~798            | 42                 |     | 48   | dB   |
| 6   |              |                         | 807~915            | 41                 |     | 47   | dB   |
| 7   |              |                         | 925~960            | 40                 |     | 46   | dB   |
| 8   |              |                         | 1427~1463          | 35                 |     | 41   | dB   |
| 9   |              |                         | 1626.5~1660.5      | 40                 |     | 45   | dB   |
| 11  |              |                         | 1695~1785          | 32                 |     | 38   | dB   |
| 12  |              |                         | 1850~2025          | 30                 |     | 36   | dB   |
| 13  |              |                         | 2300~2400          | 28                 |     | 33   | dB   |
| 14  |              |                         | 2400~2483          | 28                 |     | 33   | dB   |
| 15  |              |                         | 2500~2690          | 25                 |     | 32   | dB   |
| 16  |              |                         | 3400~3800          | 22                 |     | 29   | dB   |
| 17  |              |                         | 4400~4900          | 21                 |     | 28   | dB   |
| 18  |              |                         | 5150~5925          | 15                 |     | 22   | dB   |
| 19  |              |                         | VSWR               | 1164~1189 (Input)  |     | 2.0  | 1.4  |
| 20  |              | 1164~1189 (Output)      |                    |                    | 2.0 | 1.4  |      |
| 21  |              | Input Signal Level      |                    | MAX: +13 dBm 2000h |     |      |      |

## Frequency Performance

### Frequency Response



深圳市麦捷微电子科技股份有限公司


地址：深圳市龙华新区观澜街道高尔夫大道裕新路 65 号

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

# VSWR



深圳市麦捷微电子科技股份有限公司

地址：深圳市龙华新区观澜街道高尔夫大道裕新路 65 号


电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110


## 6 包装 Packaging

### ① 编带尺寸 Dimensions of Tape:



### ② 带轮尺寸 Dimensions of Reel


Unit: mm



|   |          |
|---|----------|
| A | 178±2    |
| B | 60±2     |
| C | 13.0±0.5 |
| D | 21.0±0.8 |
| E | 2.0±0.5  |
| W | 8.5±1.0  |
| t | 1.2±0.2  |
| R | 1.0±0.25 |

Reel material: PS (Polystyrene)

### ③ 编带简图及拉伸方向 Taping figure and drawing direction:



深圳市麦捷微电子科技股份有限公司


地址: 深圳市龙华新区观澜街道高尔夫大道裕新路 65 号

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

④ 盖带的剥离强度 Peeling strength of cover tape:



测试条件 Test condition:

- 1) 剥离角度 peel angle: 165°~180° vs. carrier tape.
- 2) 剥离速度 peel speed: 300mm/min±10%.

⑤ 包装数量 Packaging quantities: 5000 PCS / Reel


## 7 装箱清单及标志 Packing documents and marking

① 包装文件 Packing documents

- a. 装箱清单 Packing list.
- b. 合格证书 Certificate of compliance.

② 盘上标记 Marking on reels:

- a. 麦捷料号 MICROGATE Part No.
- b. 生产批号 Lot number
- c. 盘装数量 Quantity per reel
- d. 检验员号 Inspector No.



以上内容必须在标签上注明.All above shall be shown on marking label

麦捷公司标签如下所示: MICROGATE marking label will be as following:

| MICROGATE         |           |          |
|-------------------|-----------|----------|
| CUSTOMER:         | P. O. NO  |          |
| CUSTOMER PART NO: | DATE CODE | LOT NO   |
| MG PART NO:       | QUANTITY  | INSP. NO |

**MG PART NO**

深圳市麦捷微电子科技股份有限公司



地址: 深圳市龙华新区观澜街道高尔夫大道裕新路 65 号

电话(Tel): 0755-28085000

传真(Fax): 0755-28085605

邮编(Postcode): 518110

检验合格后,检验员在标签上盖上合格章。合格章如下所示: The eligible reels will be pressed a mark onto the surface. The mark will be as following:




③ 内包装盒标记:Marking on inner box

- a.型号 MICROGATE part No.
- b.每盒数量 Quantity per box
- c. 包装日期 Date

以上内容必须在标签上注明(标签见 7.2 所示)。Above shall be shown on marking label (The marking label is shown in item 7.2).

④ 外包装箱标记 Marking on outer case:

- 1) 制造商 Manufacturer: “MICROGATE” ①
- “中国深圳制造” “Made in Shenzhen CHINA”②
- 2) 发运标记 Ship marking:  
“向上” “UP”, “小心轻放”“HAND CARE”, “防潮”“MOISTURE-PROOF”.
- 3) 包装标签包括以下内容 Packing label include the following:
  - a.型号 MICROGATE Part No
  - b.总数量 Total quantity per case
  - c.包装日期 Date;



以上内容必须在标签上注明。(参见 7.2 所示)

All above shall be shown on marking label. (The marking label is shown in item 7.2)

## 8 保管 Storage

### 保存条件 Storage conditions

- 存放货物的库房应满足以下条件 Products should be storage in the warehouse on the following conditions

温度 Temperature:  $\leq 40^{\circ}\text{C}$

湿度 Humidity :  $\leq 70\%$  relative humidity

不允许温、湿度有极剧变化。No rapid change on temperature and humidity

- 禁止将产品保管在腐蚀性物质中，例如硫磺、氯气或者酸，否则将引起端头氧化，导致降低焊接性。

Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solder ability.

- 为了避免受潮气、灰尘等物质的影响，产品应保管于货架上。Products should be storage on the palette for the prevention of the influence from humidity, dust and so on.

- 产品保管在库房中时，应避免热冲击，振动以及直接光照等等。Products should be storage in the warehouse without heat shock, vibration, and direct sunlight and so on.

- 产品应密封包装 Products should be storage under the airtight packaged cond